



TECHNICAL SHEET

SIATA

ELECTRONIC CONTROLLER
SFE





SIATA ELECTRONIC CONTROLLER SFE



TECHNICAL CHARACTERISTICS

- Can be used on different valves for softening or filter applications: V132, V230, V240, V250, V260, V360, V350/V351 and V363
- Easy and simple, user-friendly programming
- LCD display backlit during programming mode
- Indication of day of the week and time of the day in hours and minutes
- Time of day alternating with volume remaining during service
- Regeneration steps and cycle time remaining
- Quick and easy setup of capacity, regeneration time, and day override
- Advanced programming options including up to 4 regenerations phases with independently adjustable cycle times
- Manual regeneration, meter immediate or delayed, time clock, day of week regeneration
- High frequency regeneration (every 1/2/3/4/6/8 or 12 hours)
- Programming is stored in the EEPROM and will not be lost due to power outages
- Interchangeable standard lithium battery (#CR2032)
- Statistic Modes
- Chlorine cell driver or external solenoid valve driver option
- Electrical rating: 230 V /50 or 60Hz transformer 12 VAC (6 VAC if Chlorine cell)
- Operating temperature range: 2-43°C

Distributed by:



S.I.A.T.A Asia Pacific Pte Ltd

37 Tannery Lane
#06-08 Tannery House
Singapore 347790
Tel: +65 6741 2994 • Fax: +65 6741 2995

www.siata.com.sg

contact: siata@siata.com.sg