



# TECHNICAL SHEET

## **SIATA** SFE-EV PRO CONTROLLER





## SIATA SFE-EV PRO CONTROLLER

### TECHNICAL CHARACTERISTICS



- Can be used on all SIATA valves for softening or filter applications, both in simplex or **duplex mode**
- Easy and simple, user-friendly programming
- Coloured LCD display:
  - High customization possibilities: customer logo, service phone number and password
  - Time of day alternating with volume remaining during the service
  - Salt status indicator
  - Indication of day of the week and time of the day in hours and minutes
  - Regeneration steps and cycle time remaining
- Easy and simple, user-friendly programming:
  - Different volume units set (liters, cubic meters or gallons)
  - Quick and easy setup of capacity, regeneration time, day override
  - Advanced programming options including up to 9 regenerations phases with independently adjustable cycle times
  - Cam on demand for customized applications
- 3 free contact relays, each one programmable in 12 different modes (for solenoid valve, dosing pump, ...)
- Modular functionality in duplex mode for higher volume demand
- Manual regeneration, meter immediate or delayed, time clock, day of week regeneration
- High frequency regeneration (every 2/3/4/6/8 or 12hours)
- Remote start, immediate or delayed, inhibit
- Statistic Modes
- Programming is stored in the EEPROM and will not be lost due to power outages
- Interchangeable standard lithium battery (#CR2032)

#### Distributed by:



**S.I.A.T.A Asia Pacific Pte Ltd**

37 Tannery Lane  
#06-08 Tannery House  
Singapore 347790

Tel: +65 6741 2994 • Fax: +65 6741 2995

**www.siata.com.sg**

contact: [siata@siata.com.sg](mailto:siata@siata.com.sg)